

~~SECRET~~

SAA200075580000
DOCUMENT #

LA-12624-MS

This document consists of 54 pages

UNCLASSIFIED

*Interim Storage of Excess Plutonium:
An Assessment of Options (U)*

John M. Haschke
Joseph C. Martz

June 17, 1993

SANITIZED
COPY

~~NUCLEAR WEAPON DATA~~

Critical Nuclear Weapon
Design Information
DoD Directive 5210.2 Applies

~~RESTRICTED DATA~~

~~This document contains Restricted Data as
defined in the Atomic Energy Act of 1954.
Unauthorized disclosure subject to
administrative and criminal sanctions.~~

Derivative Classifier
George M. Biggs
FSS-16 Classification Analyst

Los Alamos Los Alamos National Laboratory
Los Alamos, New Mexico 87545
Los Alamos National Laboratory is operated by the University of California for
the United States Department of Energy under contract W-7405-ENG-36.

~~SECRET~~

UNCLASSIFIED

96SADDA0001121

~~SECRET~~

June 17, 1993

UNCLASSIFIED

*This work was supported by the US Department of Energy,
Office of Defense Programs.*

An Affirmative Action/Equal Opportunity Employer

NOTICE

*Reproduction of this document requires the written consent of
the originator, the originator's successor, or higher authority.*

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither The Regents of the University of California, the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise, does not necessarily constitute or imply its endorsement, recommendation, or favoring by The Regents of the University of California, the United States Government, or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of The Regents of the University of California, the United States Government, or any agency thereof.

~~SECRET~~ UNCLASSIFIED

~~SECRET~~

June 17, 1993

UNCLASSIFIED

SAP 2000 7558000
DOCUMENT#

Interim Storage of Excess Plutonium:

An Assessment of Options (U)

by

John M. Haschke

Joseph C. Martz

June 17, 1993

~~RESTRICTED DATA~~
Sigma 2

Critical Nuclear Weapon
Design Information
DoD Directive 5210.2 Applies

~~RESTRICTED DATA~~

This document contains Restricted Data as
defined in the Atomic Energy Act of 1954.
Unauthorized disclosure subject to
administrative and criminal sanctions.

Derivative Classifier
George M. Biggs
FSS-16 Classification Analyst

DEPARTMENT OF ENERGY DECLASSIFICATION REVIEW	
1ST REVIEW-DATE: 9-19-96	DETERMINATION (CIRCLE NUMBER(S))
AUTHORITY: <input type="checkbox"/> AOC <input type="checkbox"/> ADC <input type="checkbox"/> ADD	<input checked="" type="checkbox"/> 1. CLASSIFICATION RETAINED
NAME: <i>Haschke, J. M.</i>	<input type="checkbox"/> 2. CLASSIFICATION CHANGED TO:
2ND REVIEW-DATE: 1-6-97	<input type="checkbox"/> 3. CONTAINS NO DOE CLASSIFIED INFO
AUTHORITY: ADD <i>Haschke</i>	<input type="checkbox"/> 4. COORDINATE WITH:
NAME: <i>Haschke</i>	<input type="checkbox"/> 5. CLASSIFICATION CANCELLED
	<input type="checkbox"/> 6. CLASSIFIED INFO BRACKETED
	<input type="checkbox"/> 7. OTHER (SPECIFY):

UNCLASSIFIED

~~SECRET~~

~~SECRET~~

June 17, 1993

UNCLASSIFIED

Table of Contents

0. Abstract	5
1. Introduction	6
2. Description of Storage Options	7
2.1 Storage as Intact Pits	7
2.2 Storage as Altered Pits	8
2.2.1 Mechanical Methods	8
2.2.2 Physical Methods	8
2.2.3 Chemical Methods	8
2.3 Storage as Extracted Material	9
2.3.1 Chemical Options	9
2.3.2 Dilution Options	10
3. Technical Evaluation of Storage Options	10
3.1 Storage as Intact Pits	10
3.2 Storage as Altered Pits	12
3.2.1 Mechanical Methods	13
3.2.2 Physical Methods	15
3.2.3 Chemical Methods	15
3.3 Storage as Extracted Material	19
3.3.1 Chemical Reactivity	20
3.3.2 Radiolytic Reactivity	21
3.3.3 Helium Release	22
3.3.4 Container Pressurization	22
3.3.5 Release of Plutonium to the Environment	23
3.3.6 Other Environmental, Safety, and Health Issues	25
3.3.7 Process Technologies	26
3.3.8 Packaging	26
3.3.9 Materials Control and Accountability	27
4. General Technical Issues	28
4.1 Reuse and Reconstitution	28
4.2 Waste Generation	31
4.3 Contingencies for Ultimate Disposition	33
4.4 Transparency	33
5. Conclusions	34
6. Recommendations	38
7. References	41

UNCLASSIFIED

~~SECRET~~

~~SECRET~~

June 17, 1993

1. INTRODUCTION UNCLASSIFIED

Recent agreements with Former Soviet Union (FSU) states will result in the removal of approximately 17,000 nuclear weapons from the active stockpile.¹ This development will dramatically alter the nuclear materials economy. In past decades, the weapons complex has been driven by frequent nuclear material shortages. However, the future will be characterized by an excess of plutonium. As such, storage of plutonium from these weapons has become one of the most important challenges for the nuclear weapons establishment. The nuclear materials effort must be redirected from one with emphasis on production and reprocessing of plutonium for stockpile needs to one with emphasis on maintenance of the enduring stockpile and on dismantlement of weapons and management of excess plutonium.²

Interim storage of excess plutonium is complex and includes both technical and political issues. Three general options have been identified for storage of excess material: (1) storage as intact pits, (2) storage as altered pits, and (3) storage in a suitable material form after extraction from the pit.^{3,4} An adequate evaluation of these options must consider technical capability as well as facility requirements and availability. Differences in pit design (e.g., an outer container of stainless steel for certain units and beryllium outer shells for others) must be considered. Generation of radioactive waste is a particularly important component of environmental, health, and safety (ES&H) concerns related to these storage options. Additional issues with strong technical and political implications include rearmament and proliferation concerns. As a result, materials control and accountability (MC&A), transparency, and safeguards and security must also be addressed.

Readiness requirements and the time frame encompassed by "interim storage" are important factors for evaluating technical options. Both durations are somewhat uncertain. Implementation of various technical options within a period as short as 2 years has been initially suggested, while various time frames from 5 to 15 years have been subsequently proposed.⁵ Technical options must also be examined in light of an interim storage period that will likely span several decades and could extend to as much as 100 years.

The focus of this report is a comprehensive technical evaluation of potential storage methods identified in a complex-wide assessment of storage options sponsored by the Department of Energy Arms Control and Nonproliferation office (AN).⁶ As participants in that study, we encountered a wide diversity of opinion regarding the merits and suitability of various storage alternatives. As the coordinators of the DOE-AN study

~~SECRET~~

UNCLASSIFIED

UNCLASSIFIED
~~SECRET~~

June 17, 1993

found, a comprehensive and internally-consistent report is difficult to prepare from input provided by several contributors with diverse perspectives. A credible report on plutonium storage must consider all pertinent information on physical and chemical properties of materials, the maturity levels of candidate technologies, potential hazards and complications associated with storage options, requirements for certification and packaging, and surveillance and monitoring of stored material. A comprehensive assessment must include relevant information from earlier studies by qualified experts as well as all potential options from diverse sources. Conflicting perspectives must be addressed. For example, non-proliferation advantages cited for certain chemically altered storage forms are inconsistent with a consensus of technical opinion stating that those materials can be used as nuclear explosives and that they are easily reconstituted to plutonium metal. Since our analysis focuses on technical issues, discussions of such topics as the process capability of specific facilities, material control and accountability (MC&A) issues, safeguards and security, and transparency concerns are limited. We attempt to identify and evaluate a range of technical issues associated with various options proposed for interim storage. Such an evaluation of storage forms cannot be divorced from the procedures and conditions required to obtain and certify those forms or from the procedures and conditions required to reconstitute the plutonium into a form suitable for fabricating a nuclear device.

2. DESCRIPTION OF STORAGE OPTIONS

2.1 Storage as Intact Pits

Storage of intact pits is an approach that employs the intrinsic characteristics that made the pit suitable for extended stockpile storage in a nuclear weapon. For an "intact" configuration, tubes might be coiled and immobilized to prevent torquing motion which could break welds or joints.⁷ Although the title of this storage category seems to preclude any alteration of the pit, the possibility of removing tubulation has been suggested as a procedure to facilitate packaging. Additional storage options appear in the packaging configuration. Issues include the number and specifications for barriers between the pit and the ambient environment, and whether pit containers are stored within insulated shipping containers.

~~SECRET~~
UNCLASSIFIED

~~UNCLASSIFIED~~
~~SECRET~~

June 17, 1993

2.2 Storage as Altered Pits

DOE b(3)

remains as a containment vessel. Two levels of alteration are recognized: (1) denying direct reuse of the pit in a nuclear device by mechanical or physical alteration, and (2) altering the utility of the nuclear material by chemical methods that make reconstitution (recovery and reprocessing) of the plutonium prohibitively difficult.

2.2.1 Mechanical Methods.

DOE b(3)

2.2.2 Physical Methods.

DOE b(3)

2.2.3 Chemical Methods.

DOE b(3)

~~SECRET~~
UNCLASSIFIED

UNCLASSIFIED
~~SECRET~~

June 17, 1993

DOE b(3)

2.3 Storage as Extracted Material

Storage of extracted material is considered attractive by some because of the potential to destroy the pit configuration and prevent easy reconstitution. The variety of candidate forms considered for interim storage include metals (unalloyed and alloyed), plutonium compounds, and mixtures. In all cases, the pit is bisected to gain access to plutonium. Extraction processes are used to separate the plutonium from other pit components prior to processing to the desired material form.

2.3.1 Chemical Options. In certain options, plutonium is stored as unalloyed metal.

DOE b(3)

~~SECRET~~
UNCLASSIFIED

~~UNCLASSIFIED~~
~~SECRET~~

June 17, 1993

The temperature of plutonium components in storage is an important parameter that is strongly influenced by the self-heating properties of plutonium.²⁴

DOE b(3)

Stringent constraints on storage temperature are anticipated for pits retained for possible reuse in weapon manufacture. Confidence in the integrity of reuse pits would be compromised if temperatures exceeded the 65–70°C range for storage of stockpile weapons. This constraint reflects a limited experience with long-term storage of plutonium metal outside of this temperature range. Problems with unknown aging effects in reuse pits would be compounded by high-temperature storage.

Storage temperature is not the only constraint for intact pit storage. The potential for plutonium release during an accident in transport or storage is of foremost concern. Plutonium in pits is potentially released by a number of mechanisms: mechanical breach, low-melting eutectic formation, and atmospheric oxidation. Transport and storage containers are designed to preserve structural integrity to the pit and prevent release by mechanical breach. Mitigation of other release hazards requires a different approach. A fire that produces temperatures in excess of the plutonium melting point (640°C) poses a hazard for release and dispersal of nuclear material.

DOE b(3)

~~SECRET~~~~UNCLASSIFIED~~

~~UNCLASSIFIED~~
SECRET

June 17, 1993

DOE b(3)

All pits to be removed from stockpile have ultimate containment layers of either beryllium or steel.

Other pit-specific storage requirements must be considered. In addition to differences in metallurgical phase, plutonium content, heat generation, and outer confinement material, important pit features include size, number and position of tubes, and the possible inclusion of neutron generators containing tritium or ^{238}Pu . Each of these variables influences the packaging configuration. For example, fixtures for constraining pit and tube movement and for dissipating heat during storage are required for each of the 10-15 pit types in the dismantlement schedule. Likewise, development of individualized surveillance programs is essential for establishing the suitability of each pit type for continued storage and for identifying those types requiring remedial action or disassembly.

DOE
b(3)

3.2 Storage as Altered Pits

Effectiveness of alteration or deformation as a denial method can only be determined on the basis of yield calculations for each deformed pit. The level of yield reduction must be considered if denial is the ultimate goal

~~SECRET~~
UNCLASSIFIED

UNCLASSIFIED
~~SECRET~~

June 17, 1993

DOE

b(3)

3.2.1 Mechanical Methods. In mechanical alteration, the pit serves as a containment vessel after deformation or dudding procedures. Concerns regarding packaging requirements, temperature limits, and fire scenarios are similar to those outlined for intact pits. Additional concerns include maturity and general applicability of the technologies, recertification of the pit as a container, and effectiveness of the denial process. Although simple in concept, mechanical deformation methods are not extensively developed and generally applicability to all pit types is uncertain.

DOE

b(3)

~~SECRET~~
UNCLASSIFIED

UNCLASSIFIED
~~SECRET~~

June 17, 1993

DOE

b(3)

Regardless of the method of mechanical denial, an appropriate level of surveillance is necessary to ensure long-term stability and containment of plutonium.

DOE b(3)

particular concern for dudding masses because of potential difficulties in welding or pinching due to residues which might remain on tube walls after injection of material.

~~SECRET~~
UNCLASSIFIED

UNCLASSIFIED
~~SECRET~~

June 17, 1993

~~SECRET~~
UNCLASSIFIED

UNCLASSIFIED
~~SECRET~~

June 17, 1993

~~SECRET~~
UNCLASSIFIED

UNCLASSIFIED
~~SECRET~~

June 17, 1993

DOE b(3)

Some have suggested that hydride intermediates might spontaneously form the desired alloy at low temperatures. This seems doubtful. Extensive experiments conducted with freshly prepared plutonium hydride and plutonium metal powders in thin (0.25 mm thick) Al foil containers at temperatures up to 500°C show no evidence of alloying.⁵⁹ A possible explanation for this observation is provided by thermodynamic data for the hydride⁶⁰ and for intermetallic compounds of plutonium.⁶¹ Although enthalpies and free energies of formation are not available for the specific alloys of interest, values reported for compounds of other elements (e.g., Fe, Rh, Ru, Pt, etc.) suggest that Al and Cu will not react with PuH_x because of unfavorable thermodynamics (i.e., PuH_x is more stable than the alloys) or will occur with production of insufficient amounts of heat to drive a self-sustained alloying process. These results are consistent with unsuccessful efforts to initiate reaction between PuH_x and low-melting-point metals.⁶²

DOE b(3)

~~SECRET~~
UNCLASSIFIED

UNCLASSIFIED
~~SECRET~~

June 17, 1993

DOE 6(3)

Although conversion of plutonium metal to other chemical forms reduces certain ES&H concerns (e.g., corrosion of steel containers during a fire), the risk of dispersing plutonium into the environment may be increased by chemical alteration.

DOE 6(3)

3.3 Storage as Extracted Material

Flexibility in storage options is increased if plutonium is removed from the pit containment vessel. Restrictions on storage temperature are less stringent because material expansion can be accommodated and fire resistance can be incorporated in container design. Difficulties and constraints associated with *in situ* formation of compounds (hydride, oxide, nitride, alloys, etc.) are significantly reduced by not relying on the pit container to serve as a reaction vessel. However, extraction of plutonium from the pit allows material to more readily contact other chemical species in the process environment. As discussed in sections 3.3.2 and 3.3.4, the potential consequences of such exposures are strongly influenced by the physical properties (such as surface area) of the storage form. Since a technical evaluation related to storage of extracted material is most conveniently addressed by focusing on issues instead of material form, that format is adopted for this section.

- 19 -
~~SECRET~~
UNCLASSIFIED

~~UNCLASSIFIED~~
~~SECRET~~

June 17, 1993

3.3.2 Radiolytic Reactivity. Radioactive decay of plutonium alters the chemical behavior and makeup of molecular and organic compounds in a storage vessel and may alter the stored material or lead to loss of containment.⁷⁹ Radiolytic chemistry is influenced by particle dimension as well as isotopic composition and age of the plutonium. Powdered samples emit a large fraction of the 5.1 MeV alpha decay particles, the primary initiator of radiolytic reactivity for ²³⁹Pu. Recall the high surface area of finely divided plutonium compounds promotes adsorption of large amounts of water, organic molecules etc. As such, alpha particles from radioactive decay have ample opportunity to interact with adsorbed species in the storage environment. The presence of adsorbates is not limited to fine powders: adsorption is observed for all candidate materials because of facile formation of surface oxide. However, the quantity of adsorbate on massive samples such as alloys or metal is small compared to PuO₂ and other finely divided forms. Dioxide products with specific surface areas in excess of 50 m²/g are common.^{80,81} When exposed to ambient glovebox atmospheres for several hours, the mass of a typical oxide sample may increase by more than 1 % due to water adsorption.⁸²

Interaction of alpha particles with adsorbed species, organic materials (e.g., plastics), or gases in contact with the nuclear material leads to chemical bond cleavage and formation of gaseous products.^{83,84,85} Low-molecular-weight species (e.g. O₂ and N₂) primarily dissociate to form gaseous products (e.g., NO₂), while heavier molecules tend to polymerize. Radiolysis of water generates hydrogen and oxygen;^{86,87} alpha interaction with air produces large percentages of dinitrogen monoxide (N₂O) and nitrogen dioxide (NO₂).⁸⁸ Products formed by radiolysis of plastics and other organic materials depend on their chemical composition and typically include hydrogen.⁸⁹ Radiolytic decomposition of polyvinyl chloride (PVC) apparently forms gaseous hydrogen chloride (HCl).

DOE b(3)

~~SECRET~~

UNCLASSIFIED
~~SECRET~~

June 17, 1993

DOE
b(3)

In sum, the magnitude of radiolytic effects is influenced by two important properties of the material to be stored: the specific surface area (and the associated quantity of adsorbates), and the ability of the material to getter radiolytic products. In both cases, plutonium metal and alloys are expected to have considerably fewer problems with radiolytic phenomena than more finely divided Pu forms.

3.3.3 Helium Release. Helium formed by alpha decay of ^{239}Pu and other isotopes provides an additional source for pressure generation during storage. Although the process is slow ($t_{1/2} = 2.4 \times 10^4$ years), the quantity of helium may become significant if the storage period is long and the fraction of He released by the solid phase is large. The release behavior of massive metal differs from that of oxide because the diffusion rate of He in metal is relatively slow and hence, He is only able to escape from the near-surface region of the solid. By contrast, diffusion of He in oxide is comparatively rapid and the small particle dimensions allow the ready release of all helium created by alpha decay. Experimental data for both ^{238}Pu and ^{239}Pu show that helium is readily released from oxide^{90,91} but is retained as microscopic bubbles at grain boundaries of Pu metal.⁹²

Calculations based on the alpha decay rate and helium release kinetics of metal and oxide show that He pressures greater than one atmosphere are anticipated for oxide in a typical storage configuration after 100 years.⁹³ By comparison, the pressure rise expected for storage of an equivalent amount of metal is approximately 0.001 atmosphere. Although the He release behavior of massive alloys and non-metallic powders is expected to parallel those of the metal and oxide, experimental data are not available.

3.3.4 Container Pressurization

DOE
b(3)~~SECRET~~
UNCLASSIFIED

~~UNCLASSIFIED~~
~~SECRET~~

June 17, 1993

DOE

b(3)

3.3.5 Release of Plutonium to the Environment. From both environmental and political perspectives, release of plutonium-containing materials to the environment is a serious potential hazard. The two most likely situations that may lead to release are mechanical breach of a storage container and exposure to a fire. Once plutonium has been released to the environment, further spread of material is of prime concern. As such, the dispersal risks associated with various forms is directly related to the particle size and form of the material.⁹⁹

DOE

b(3)

~~SECRET~~
~~UNCLASSIFIED~~

~~UNCLASSIFIED~~
~~SECRET~~

June 17, 1993

In contrast to metal or alloys, relatively large fractions of finely-divided forms are in the dispersible range.¹⁰³ 20–25 mass% of the PuO_2 formed by oxidation of the hydride consists of particles with dimensions less than $10\text{ }\mu\text{m}$,¹⁰⁴ while 100 mass% of the oxide formed by pyrolysis of precipitates (e.g., hydrated plutonium oxalate) from aqueous processing is in this dispersible range.¹⁰⁵

DOE 6L3)

Upon release of plutonium metal to the ambient environment, the potential for oxidation and subsequent dispersal by aerosolization exists. The oxidation rate of Pu in air at 500°C and above is modest and constant ($0.2\text{ g PuO}_2/\text{cm}^2 \cdot \text{min}$ of metal surface).¹⁰⁷ The oxide product formed at these temperatures is relatively coarse with less than 0.1 mass% in the dispersible range.¹⁰⁸

Although container corrosion may also occur during a fire involving stored hydride, the possibility of container rupture exists for other powdered forms because of increased gas evolution and pressure and decreased container strength at high temperatures. The pressure is a combined effect arising from chemical reaction, radiolytic decomposition, helium release, thermal desorption, and thermal expansion. Rupture is expected to result in the dispersal of a larger fraction of powdered forms than would be released from massive metal or alloys.

On the basis of relative particle size distributions, the quantity of plutonium-containing material released to the environment is 1,000 to 10,000 times greater for finely-divided material forms than for massive metal. The risk of corrosion and container failure are likely reduced for alloy storage, but the potential hazard posed by such storage can not be assessed because information on reaction rates, thermodynamics, and particle distributions are not available.

Remediative actions can be employed to reduce the risks associated with containment of metal and powdered forms during a fire. Application of a ceramic coatings on internal container surfaces (e.g., erbium oxide)¹⁰⁹ or insertion of reactive container liners that alloy and chemically immobilize plutonium as a high-melting compound (e.g., aluminum)¹¹⁰

~~SECRET~~
UNCLASSIFIED

would greatly reduce the risk of metal release during a fire. The possibility of pressurization could also be reduced for powdered materials by certification to verify that significant quantities of adsorbates are not present.¹¹¹

Use of vented containers for powder storage must be evaluated in light of reduced container structural integrity and the consequences of radiolysis-enhanced corrosion of the nuclear material or the container. Formation of nitrogen oxides from air in a radiolytic environment produces nitric acid if water is also present.¹¹² Mass measurements for oxide stored in vented stainless-steel containers show a mass increase of 2-3% after several years.¹¹³ Reasons for these changes are not known, though the possibility of container oxidation catalyzed by radiolytically-formed nitric acid is under investigation. Rupture disks which function only on pressurization may alleviate the risk of catastrophic container failure during fires or other accidents while preventing exposure of the nuclear material to external ambient storage environments under normal conditions.

3.3.6. Other Environmental, Safety, and Health Issues. Other ES&H issues related to storage of extracted material include nuclear criticality safety, radiation exposure to personnel, and contamination control. Criticality safety procedures are well established for all candidate storage forms. Primary controls include limiting the quantity of stored material and careful inventory and control of physical storage and locations. As an added precaution, storage of plutonium metal and alloys as castings with critically-safe geometries (e.g., thin-walled rings) can reduce the possibility of a criticality incident by deliberate or accidental violation of safety procedures. Criticality safety for finely-divided forms must rely on administrative controls that establish handling procedures and mass limits.

Procedures for limiting worker radiation exposure and controlling spread of radioactive contamination have been well established in the last 40 years. However, increasingly stringent regulatory requirements are anticipated for both areas, and hence, consideration of advanced material handling technologies to reduce these exposures and risks is worthwhile. The advantage of automation in distancing operators from nuclear material and reducing the likelihood of operator error is widely recognized.¹¹⁴ Castings of metal or alloy are amenable to automated handling, as are powdered materials. Procedures differ for handling finely-divided forms and in some instances are more complex than for

UNCLASSIFIED
~~SECRET~~

June 17, 1993

transfer of discrete metal components. However, care must be taken in automation to ensure high reliability among robotic components because frequent breakdowns in automated equipment would only transfer radiation exposure from operating to maintenance personnel.

Storage of plutonium in a form containing nuclear fission products as radioactive diluants would have an enormous impact on radiation exposure levels in a typical plutonium facility.¹¹⁵ Construction of special remote handling capability would be necessary to accommodate such highly radioactive materials. Numerous vitrification plants are in operation which provide for remote process and handling of highly radioactive waste.

3.3.7. Process Technologies. Requisite processing for storage of extracted materials is contingent on the storage form(s) adopted. Constraints on volume, temperature, gas flow, and throughput that restrict *in situ* chemical disablement can be readily addressed for extracted material with appropriately designed equipment. For example, production of oxide via the $\text{PuH}_2 + \text{O}_2$ reaction is an established production process.¹¹⁶ Constraints on temperature and hydrogen removal are easily accommodated by appropriate design of process equipment. Formation of many intermetallic plutonium compounds has been demonstrated on a kilogram scale though production qualified operations have not been developed.^{117,118}

The level of development activity required to implement storage of extracted material is strongly dependent on the choice of storage form. Methods are fully developed for extended storage of metal;¹¹⁹ only transfer of technology from pit fabrication processes is necessary. Experience with storage of oxide is more limited, but the general criteria (e.g., specification of residual polyanion content, adsorbed water loading, oxide stoichiometry, etc.) for preparation of a certified oxide are known. However, procedures to achieve these criteria have yet to be developed. Requirements and technologies for preparing other candidate storage forms are poorly defined.

3.3.8. Packaging. Although specifics of container design are influenced by the storage form, basic features are similar for all options. In addition to satisfying transportation regulations and providing suitable fire resistance, *the primary container must not include organic or covalently-bound materials that might be exposed to plutonium-containing*

~~SECRET~~
UNCLASSIFIED

SECRET

June 17, 1993

UNCLASSIFIED

particles. This includes organic and other covalently bound materials introduced either intentionally (e.g., bagging or o-rings) or unintentionally (e.g., adsorbed water on oxide). A second essential requirement is that all containers be sealed (and certified as such) so that communication with the ambient atmosphere during storage is prevented. An extensive study of failures and accidents involving plutonium storage reveals that one or both of these requirements was not met in all cases examined.

3.3.9 Materials Control and Accountability. MC&A is an important technical issue because certification of the nuclear material quantity is necessary after extraction. Accountability methods typically rely on chemical analysis of "representative" samples and material mass measurements to determine plutonium content. Use of mass measurements alone is unacceptable. For example, the Pu content of "dioxide" samples prepared by precipitation from aqueous solution and calcination may be up to 10% less than the theoretical value for PuO_2 .¹²⁰

Product homogeneity is essential for obtaining representative samples and obtaining accurate analytical results. Inhomogeneity is not a severe problem for plutonium metal or for binary compounds (e.g., oxide, nitride, hydride) formed by reaction of metal with pure gases. Products formed by reaction of condensed phases or by pyrolysis of solids (e.g., carbides, intermetallic compounds, some oxides) are difficult to homogenize. The existence of multiple solid phases and slow transport processes in a chemical system introduces a series of kinetic limitations that hinder product equilibration. This results in sample inhomogeneity which leads to difficulty in determining actual plutonium content based on "grab" samples and mass measurements. Calculation of Pu content from calorimetry is not as sensitive to sample inhomogeneity, though calorimetry is not as sensitive or accurate as other assay techniques. Problems with inhomogeneity are expected to be particularly acute for plutonium stored in high-level fission waste. Verification of plutonium mass and detection of plutonium diversion would be difficult (if not impossible) with such storage forms.

Results of nondestructive assay (NDA) methods such as neutron and gamma-ray spectroscopies are also sensitive to the sample matrix. Inhomogeneity may alter the results of these measurements. Heavy elements that alter self-absorption characteristics and light elements that participate in alpha-neutron (α -n) reactions are of particular concern.¹²¹

SECRET

UNCLASSIFIED

~~UNCLASSIFIED~~
~~SECRET~~

June 17, 1993

4. GENERAL TECHNICAL ISSUES

Certain issues are common among all storage forms and options. Concerns about reuse of material, ease of reconstitution to nuclear weapons, waste generation, preservation of flexibility for ultimate final disposition, verification, and transparency of nuclear material extraction and storage are all considered here. All of these topics merit detailed, indepth evaluation far beyond that given below. As such, our discussion is to be considered cursory and is only intended to highlight the major relevant issues and how they relate to various plutonium storage options.

4.1. Reuse and Reconstitution

The motivation for disablement of pits and chemical alteration of extracted plutonium is in denying direct reuse of components and materials in a nuclear device and in making reconstitution to a usable form prohibitively difficult. A careful examination of reuse and reconstitution issues is needed to adequately assess the merits of implementing disablement or chemical conversion processes. As will be seen below, the primary advantage gained from such processes is political, not technical. While reconstitution and reuse of plutonium in any candidate form is technically simple and well within the capability of a subnational or terrorist group,¹²² the potential political message alteration or disablement sends may hold considerable value (i.e., the ability to say we have "done something" to our nuclear material such that it is no longer a "nuclear weapon").

DOE
b(3)

~~SECRET~~
UNCLASSIFIED

UNCLASSIFIED
~~SECRET~~

June 17, 1993

DOE b(3)

Further, the benefits of chemically altering pits or extracted material must be weighed against the possibility of direct reuse in device construction and the possibility of conversion of the plutonium form to one more suitable for weapon fabrication.

DOE

b(3)

~~SECRET~~

UNCLASSIFIED

UNCLASSIFIED

UNCLASSIFIED
~~SECRET~~

June 17, 1993

DOE b(3)

Advantages of extreme dilution must be weighed against the costs and the storage volume necessitated by the large quantity of material.

4.2. Waste Generation

The level of waste generation is a major consideration in assessing storage options for extracted plutonium. Though advantage is gained by upgrading process technologies, the greatest benefit is achieved by avoiding all unnecessary processing.¹³⁹ The simplest method of limiting waste generation is intuitive: leave materials in their existing form. Interconversion of material forms should be minimized to avoid waste generation and other ES&H concerns associated with material handling. However, potential problems with a particular stored material may require processing to an alternate form to alleviate concerns. Nearly all plutonium in US inventories is currently metal or oxide, with a lesser fraction stored mostly as process wastes including incinerator ash, chloride-rich salts, and aluminum-magnesium compounds (scrub alloy). The inventory existing as carbide, nitride, or hydride is small.

Certain options might be suggested to remediate anticipated storage problems. For instance, briquetting of oxide has been proposed as a method of preventing dispersion during handling and storage. Though perhaps simple in design, practical and demonstrated processes to accomplish such remediation often do not exist. All processes and alternatives must be evaluated to assess their net impact on waste generation and other ES&H concerns.

~~SECRET~~
UNCLASSIFIED

UNCLASSIFIED
~~SECRET~~

June 17, 1993

Consideration should also be given to the selection of process technologies for preparation of candidate forms. The level of waste generation varies substantially for process alternatives.]

B(3)

Some disablement options generate more waste than others!!

b(3)

A severe waste impact is encountered for dilution to less than 0.5 at.% with non-____ nuclear material such as glass.

B(3)

~~SECRET~~
UNCLASSIFIED

4.3. Contingencies for Ultimate Disposition

A consideration of possible future issues and needs is essential, especially since the decision on final disposition remains unanswered. Plutonium removed from stockpile might be required for future weapon fabrication or used as an energy source.

Alternatively, Pu might be diluted and packaged for long-term geologic disposition or monitored above-ground storage. Advantage is gained by choosing storage options that preserve maximum flexibility and provide minimum difficulty in responding to such future needs. Any option that causes problems with handling and reuse, or that causes reconstitution to be hazardous, difficult, or costly for a potential adversary will create similar problems for the custodian state.

The choice of storage form is a key factor in contingency planning. The decision is inexorably tied to the issue of waste generation. Excess weapons-grade plutonium exists almost entirely as pure metal in pits. Maintaining purity and metallic form minimizes waste generation now and in the future, while preserving flexibility for all currently suggested disposition options. Since the formation reactions of all chemical compounds from the metal are thermodynamically favored without the use of secondary reagents, the preparation of any final form is most efficiently accomplished through the use of metal. Interim storage of all plutonium compounds involves waste generation during their initial preparation for storage and during subsequent reprocessing to the final form. Separate technologies and equipment will most likely be required to prepare material for interim storage and for final disposition. The likelihood that interim and final forms will be identical is small unless a decision on ultimate disposition is made soon.

4.4 Transparency

Verification of nuclear material quantity and disposition without simultaneously divulging sensitive weapon-design or national-security information can be difficult. These problems are most acute for storage of intact or altered pits. In these cases, verification will likely rely on radiation signatures (neutron and gamma) that can be measured through the walls of a storage container or weapon case or on calorimetric measurements that can be made without disclosing component geometry. In order for such methods to be quantitative, information must be provided for the chemical and age-corrected isotopic composition of the nuclear material as well as for the relevant absorption or enhancement (α -n) characteristics of the storage configuration.

UNCLASSIFIED
~~SECRET~~

June 17, 1993

Table 1. Evaluation of Plutonium Storage Options

Option	Direct Use Possible	Easily Reconstituted	Feasible	Development Required	Applicability	Waste Generation	ES&H Concerns	Flexibility
A. Intact	yes	yes	yes	minimal	all	none	few	high
B. Altered								
DOE b(3)								
2. Inert Material (many)	yes?	yes	yes	modest	some	minimal	some	moderate
3. Reactive Material	?	yes	yes	extensive	most	high	many	moderate
	?	yes	yes	modest	all	high	some	high
DOE b(3)								
	?	yes	yes	modest	most	minimal	many	high
	?	yes	yes	extensive	most	modest	many	limited
	?	yes	no	extensive	most	modest	many	limited
	?	yes	no	extensive	many	high	some	v. limited
	?	yes	no	v. extensive	many	high	many	v. limited
C. Extracted								
1. Metal	yes	yes	yes	minimal	all - N/A	minimal	few	high
2. Oxide	yes	yes	yes	minor	"	modest	some	limited
3. Hydride	yes	yes	yes	minor	"	minimal	many	high
4. Nitride	yes	yes	yes	modest	"	modest	many	limited
5. Carbide	yes	yes	yes	extensive	"	modest	many?	limited
6. Alloys	yes?	yes	yes	extensive	"	high	many?	v. limited
7. Mixed Oxides	yes?	yes	yes	minor	"	high	few	v. limited
D. Extracted/Diluted								
1. Isotopic	yes	no	maybe	extensive	"	varies	few?	low
2. Radioactive (HLW)	no	no	yes	v. extensive	"	high	excessive	none
3. Extreme Dilution	no	no	yes	modest	"	v. high	many	minimal

UNCLASSIFIED
~~SECRET~~

UNCLASSIFIED

LA-12624-MS

~~SECRET~~

June 17, 1993

The issues examined in the first and second columns of Table I are particularly important for addressing proliferation and security concerns. The column labeled "direct-use possible" considers the possibility of using without modification the pit or altered pit in a nuclear weapon, and in the case of extracted material (section C and D) considers the possibility of using the stored, unaltered material in device fabrication. In the second column, "easily reconstituted" provides an evaluation of the difficulty in reprocessing the stored material to metallic plutonium.

DOE

b(3)

The potential advantage of this option as a non-proliferation measure must be weighed against factors such as waste generation, ES&H concerns, and flexibility which appear in the right-hand columns of Table I. Verification of nuclear material content and detection of diversion or theft is extremely difficult with this storage form. Severely diminished flexibility is a consequence of extreme or high-level waste dilution because reprocessing to other

~~SECRET~~
UNCLASSIFIED

UNCLASSIFIED
~~SECRET~~

LA-12624-MS

June 17, 1993

material forms is difficult, if not prohibitive, from an ES&H standpoint. In addition, high-level waste or extreme dilution is appropriate only if these choices are acceptable options for final disposition.

The assessment of reuse and reconstitution options in Table I leads to several important conclusions. A magical solution does not exist for solving the proliferation problems associated with storage of plutonium. Neither alteration of pits nor conversion of metal to another material form can be justified on the basis of their effectiveness as a technical nonproliferation measure. An important conclusion is that safeguards and security are essential and provide the only available technical and physical means for addressing the proliferation risk of stored excess plutonium.

Since most options in Table I are feasible, a ranking of their suitability for interim storage rests with remaining issues in Table I. A survey of the assessments show that methods for pit alteration require substantial development, are not generally applicable to all pit types, generate substantial waste, and reduce flexibility. Performance in these categories is improved for the extracted storage options outlined in Section C of Table I. However, the most attractive option remains storage of excess plutonium as intact pits.

DOE

b(3)

~~SECRET~~
UNCLASSIFIED

UNCLASSIFIED
~~SECRET~~

June 17, 1993

The preceding conclusions are supported by prior assessment and by experience in storage of various plutonium forms. In 1981, a DOE task force concluded that "metal is the best characterized, best understood, and easiest to store physical form of plutonium."¹⁴⁸ The capability for storage of plutonium metal has been developed and demonstrated during more than forty years of production and stockpile-storage of pits. Techniques for preventing corrosion of the stored metal are well established. The suitability of well-characterized metal as a storage form is evidenced by the remarkable success of thousands of "pit tests" that span a period of over thirty years for some weapon systems. Although experience in storage of weapons grade oxide is relatively limited, a substantial database exists for storage of reactor-grade material. Large quantities of oxide have been stored for up to ten years without incident. In these cases, the material was prepared, certified and packaged according to well-defined procedures. Our conclusions regarding preparing, certifying, and packaging of oxide for storage are consistent with the findings of numerous groups.^{149,150,151} When the recommended procedures have not been followed, failures and accidents have occurred. Indeed, unfavorable incidents have occurred with both metal and oxide when preparation and packaging were inadequate.

6. RECOMMENDATIONS

We recommend that excess plutonium be stored as intact pits. Development activities include definition of specifications for storage containers that accommodate all pit types. Storage containers should immobilize tubulation, have certifiable closures, maintain a safe storage temperature, and provide enhanced containment in the event of fire. Since removal of tubulation destroys the certified pit closure, tube removal must be carefully examined and may require additional development. Appropriate surveillance procedures for monitoring behavior and changes during storage can be adapted from stockpile evaluation procedures for similar pit types.

If extraction of plutonium is required for interim storage, we recommend that metal be stored as critically safe castings. Implementation of this option will benefit from development of advanced process technologies with the goal of minimizing waste and reducing radiation exposures to personnel during recovery and casting. In addition, specification and design of a storage container(s) must be completed and requisite

~~SECRET~~
UNCLASSIFIED

UNCLASSIFIED
~~SECRET~~

June 17, 1993

procedures for metal preparation, certification, and packaging must be developed and implemented. Storage facility issues, surveillance requirements, and MC&A procedures must be established.

We recommend that all weapons-grade oxide and oxide-containing residues be stored in their existing material forms during the interim period. Container specifications must be established and methods for preparation, certification, and inventory of material from diverse sources must be developed. Surveillance procedures for oxide must also be defined and established. The suitability of storing various non-oxide residues and techniques for processing those materials to storable forms should also be investigated.

If storage of extracted plutonium as metal is unacceptable due to non-technical considerations, we recommend that all plutonium be stored as oxide. Procedures must be developed to efficiently convert large quantities of metal to certified oxide with minimal waste generation.

DOE
b(3)

Our technical assessment and analysis of storage issues leads to general recommendations about packaging requirements and storage container design. Stored materials (intact pits, altered pits, extracted metal, oxide) must be well-characterized and certified. In the case of extracted materials, handling procedures must be established to ensure that integrity is preserved during packaging. Essential requirements for storage containers are strict exclusion of all reactive and radiolizable materials from the container (primarily organics and water), and isolation of stored material from the ambient atmosphere by one or more metal seals.

~~SECRET~~
UNCLASSIFIED

UNCLASSIFIED
~~SECRET~~

June 17, 1993

Examination of reuse and reconstitution issues leads to general recommendations regarding reduction of proliferation risks.

DOE

b(3)

Safeguards and security remain the primary technical means to prevent diversion and use of stored plutonium by proliferant states and sub-national groups.

~~SECRET~~

UNCLASSIFIED
~~SECRET~~

June 17, 1993

7. References

- ¹S. J. Guidice, briefing to National Academy of Sciences select committee on plutonium storage, Los Alamos, New Mexico (March 3, 1993) (U).
- ²Excess plutonium must be managed until a final decision regarding disposition is made. A discussion of final disposition options is beyond the scope of this work; this paper addresses only interim storage of material.
- ³G. Kiernan, F. Kovar, J. Robbins, A. Sunwoo, J. Haschke, J. Martz, S. Kinkead, K. Thomas, J. Markin, M. Mullin, D. Close, W. Stanbro, C. Olinger, L. Crisler, P. Burdeaux, M. Freshley, D. Finch, and W. Pardue, "Interim Storage Issues for Plutonium from Dismantled Weapons (U)," DOE-AN report, TVP-92-035 (SRD) (January 15, 1993).
- ⁴G. Bradshaw, meeting on plutonium storage options, U.S. Department of Energy, Washington, D.C. (SRD) (October 16, 1993).
- ⁵G. Bradshaw, meeting on plutonium storage options (SRD) (1992), *ibid*.
- ⁶G. Kiernan, et al., "Interim Storage Issues for Plutonium from Dismantled Weapons (U)," (SRD) (1993), *ibid*.
- ⁷R. Sharp, Los Alamos National Laboratory memorandum WX-11-92-RRS-2 (November 19, 1992) (U).
- ⁸R. Garwin, private communication at Los Alamos National Laboratory (March 4, 1993).
- ⁹J. J. Petranto, private communication at Los Alamos National Laboratory (May 4, 1993).
- ¹⁰J. J. Hayden, private communication at Los Alamos National Laboratory (May 4, 1993).
- ¹¹G. Kiernan, et al., "Interim Storage Issues for Plutonium from Dismantled Weapons (U)," (SRD) (1993), *ibid*.
- ¹²A. J. Sunwoo, L. R. Crisler, and J. L. Robbins, "Metallurgically Safeguarding Plutonium from Dismantled Weapons (U)," Lawrence Livermore National Laboratory report UCRL-LR-111673 (CRD) (November 1992).
- ¹³J. M. Haschke, H. Meyer-Christians, B. F. Flamm, J. C. Martz, and J. W. Ward, "A Hydrogen Recycle Process for Plutonium Recovery," Los Alamos National Laboratory report LA-12086-MS (UCNI) (May 1991).
- ¹⁴F. H. Ellinger, W. N. Miner, D. R. O'Boyle, and F. W. Schoenfeld, "Constitution of Plutonium Alloys," US Atomic Energy Commission report, Los Alamos, New Mexico, LA-3870 (U) (December 1968).
- ¹⁵J. M. Haschke, "Actinide Hydrides," in *Topics in f-Element Chemistry: Synthesis of Lanthanide and Actinide Compounds Volume II*, Chapter 1, G. Meyer and L. R. Morass, Eds., Kluwer Academic Publishers, Dordrecht, Netherlands (U) (1991).
- ¹⁶J. L. Stakebake, "Kinetic Studies of the Reaction of Plutonium Hydride with Oxygen," *Nucl. Sci. Eng.*, **78** (U) (1981) 386.

~~SECRET~~
UNCLASSIFIED

UNCLASSIFIED
~~SECRET~~

June 17, 1993

- ³⁶W. N. Miner and F. W. Schoenfeld, in *Plutonium Handbook Vol. I and II*, O. J. Wick, Ed., American Nuclear Society, La Grange, Ill., (U) (1980), Chapter 3.
- ³⁷J. M. Haschke, "Actinide Hydrides," in *Topics in f-Element Chemistry: Synthesis of Lanthanide and Actinide Compounds Volume II*, Chapter 1, G. Meyer and L. R. Morass Eds., Kluwer Academic Publishers, Dordrecht, Netherlands (1991).
- ³⁸J. M. Haschke and T. H. Allen, "Hydrogen Corrosion of Plutonium in Nuclear Weapons (U)," (SRD) (1992), *ibid*.
- ³⁹J. M. Haschke, A. E. Hodges, III, C. M. Smith, and F. L. Oetting, *J. Less. Com. Met.* **73** (U) (1980) 41.
- ⁴⁰H. E. Flotow, J. M. Haschke, and S. Yamauchi, "The Actinide Hydrides" in *The Chemical Thermodynamics of Actinide Elements and Compounds, Part 9*, F. L. Oetting, Ed., International Atomic Energy Agency, Vienna (U) (1984).
- ⁴¹J. M. Haschke and T. H. Allen, "Hydrogen Corrosion of Plutonium in Nuclear Weapons (U)," (SRD) (1992), *ibid*.
- ⁴²J. L. Stakebake, "Kinetic Studies of the Reaction of Plutonium Hydride with Oxygen," *Nucl. Sci. Eng.*, **78** (U) (1981) 386, *ibid*.
- ⁴³F. Brown, H. M. Ockenden, and G. A. Welch, *J. Chem. Soc.* **1955** (U) (1955) 4196, *ibid*.
- ⁴⁴T. Muromura and K. Ouchi, "Kinetic Study of the Nitrogenation of Plutonium Hydride with Ammonia," *J. Inorg. Nucl. Chem.* **38** (U) (1976) 1855, *ibid*.
- ⁴⁵J. M. Haschke, "Evaluation of Source-Term Data for Plutonium Aerosolization," (U) (1992), *ibid*.
- ⁴⁶J. L. Stakebake and H. N. Robinson, "Plutonium Release from Burning Sodium," *Nucl. Technol.* **33** (1977) 30.
- ⁴⁷J. L. Stakebake and M. H. Soba, *J. Less Com. Met.* **158** (1990) 221.
- ⁴⁸J. L. Stakebake, "Characterization of the Plutonium-Water Reaction: Reaction Kinetics Between 200 and 350°C," in *Transuranium Elements: A Half Century*, L. R. Moss and J. Ferger, Eds., American Nuclear Society, Washington D.C. (U) (1992), chapter 27.
- ⁴⁹J. M. Haschke, A. E. Hodges, III, G. E. Bixby, and R. L. Lucas, "The Reaction of Plutonium with Water: Kinetics and Equilibrium Behavior of Binary and Ternary Phases in the Pu+O+H System," Rockwell International report RFP-3416, Golden, Colorado (U) (February 1983).
- ⁵⁰J. M. Haschke, "Hydrolysis of Plutonium: the Plutonium Oxygen Phase Diagram," in *Transuranium Elements: A Half Century*, L. R. Moss and J. Ferger, Eds., American Nuclear Society, Washington D.C. (U) (1992), chapter 40.
- ⁵¹J. L. Stakebake and M. R. Dringman, "Hygroscopicity of Plutonium Dioxide," Dow Chemical Company report RFP-1056, Golden, Colorado (U) (January 1968).

~~SECRET~~
UNCLASSIFIED

UNCLASSIFIED
~~SECRET~~

June 17, 1993

- ⁵²J. L. Stakebake and L. M. Steward, "Water Vapor Adsorption on Plutonium Dioxide," *J. Colloid Interface Sci.* **42** (U) (1973) 581.
- ⁵³J. L. Stakebake and M. R. Dringman, "Desorption from Plutonium Dioxide," Dow Chemical Company report RFP-1248, Golden, CO (U) (November 1968).
- ⁵⁴J. L. Stakebake, "A Thermal Desorption Study of the Surface Interactions between Water and Plutonium Dioxide," *J. Phys. Chem.* **77** (U) (1973) 581.
- ⁵⁵A. J. Sunwoo, et al., "Metallurgically Safeguarding Plutonium from Dismantled Weapons (U)," (CRD) (1992), *ibid.*
- ⁵⁶F. H. Ellinger, et al., "Constitution of Plutonium Alloys," (U) (1968), *ibid.*
- ⁵⁷O. J. C. Runnels, "Phase Equilibria in the Aluminum-Plutonium Systems," in *Plutonium 1965*, A. E. Kay and M. B. Waldron, Eds., Chapman and Hall, London (U) (1965), p. 341.
- ⁵⁸T. B. Rhinehammer, D. E. Etter, and L. V. Jones, "The Plutonium-Copper Phase Diagram," in *Plutonium 1960*, E. Grison, W. B. H. Lord, and R. D. Fowler, Eds., Cleaver-Hume Press Ltd, London (U) (1961), p. 289.
- ⁵⁹J. M. Haschke, "Thermodynamic Properties of the Cubic Plutonium Hydride Solid Solution," Rockwell International report RFP-3099, Golden, Colorado (U) (December 1981).
- ⁶⁰H. E. Flotow, et al., "The Actinide Hydrides" in *The Chemical Thermodynamics of Actinide Elements and Compounds, Part 9*, (U) (1984), *ibid.*
- ⁶¹J. W. Ward, P. D. Kleinschmidt, and D. E. Peterson, "Thermodynamic Properties of the Actinide Elements and Selected Actinide-Noble Metal Intermetallics," in *Handbook of Physics and Chemistry of the Actinides Vol. 4*, A. J. Freeman and C. Kelley, Eds., Elsevier Science Publishers, Amsterdam (U) (1986), Chapter 7.
- ⁶²J. M. Haschke and R. L. Lucas, "The Interaction of Plutonium Hydride with Woods-Type Alloys (U)," Rockwell International report CD85-6045, Golden, Colorado (U) (December 1985).
- ⁶³F. H. Ellinger, et al., "Constitution of Plutonium Alloys," (U) (1968), *ibid.*
- ⁶⁴A. J. Sunwoo, et al., "Metallurgically Safeguarding Plutonium from Dismantled Weapons (U)," (CRD) (1992), *ibid.*
- ⁶⁵F. Kovar, conference on plutonium storage issues, Lawrence Livermore National Laboratory, Livermore, California (SRD) (February 5, 1993).
- ⁶⁶H. E. Flotow, et al., "The Actinide Hydrides" in *The Chemical Thermodynamics of Actinide Elements and Compounds, Part 9*, (U) (1984), *ibid.*
- ⁶⁷J. M. Haschke, "Evaluation of Source-Term Data for Plutonium Aerosolization," 1992, *ibid.*
- ⁶⁸J. L. Stakebake, "The Storage Behavior of Plutonium Metal, Alloys, and Oxide. A Review," *J. Nucl. Mat.* **38** (U) (1971) 241.

~~SECRET~~
UNCLASSIFIED

UNCLASSIFIED
~~SECRET~~

June 17, 1993

- ⁶⁹C. A. Colmenares, "Oxidation Mechanisms and Catalytic Properties of the Actinides," *Prog. Solid State Chem.* **9** (U) (1984) 257.
- ⁷⁰J. L. Stakebake, D. T. Larson, and J. M. Haschke, "Characterization of the Plutonium-Water Reaction II: Formation of a Binary Oxide Containing Pu(VI)," *J. Alloys Comp.*, **202** (1993) 251, Los Alamos National Laboratory document LA-UR-93-0040 (U).
- ⁷¹J. L. Stakebake, "Plutonium Pyrophoricity," EG&G Rocky Flats Division report RFP-4517, Golden, Colorado (U) (June 1992).
- ⁷²J. M. Haschke, "Actinide Hydrides," in *Topics in f-Element Chemistry: Synthesis of Lanthanide and Actinide Compounds Volume II*, Chapter 1, G. Meyer and L. R. Morass, Eds., Kluwer Academic Publishers, Dordrecht, Netherlands (U) (1991).
- ⁷³J. M. Cleveland, *The Chemistry of Plutonium*, 1979, *ibid.*
- ⁷⁴J. D. Moseley and R. O. Wing, "Properties of Plutonium Dioxide," Dow Chemical Company report RFP-503, Golden, Colorado (U) (August 1965).
- ⁷⁵J. L. Stakebake and M. R. Dringman, "Hygroscopicity of Plutonium Dioxide," (U) (January 1968), *ibid.*
- ⁷⁶J. L. Stakebake and L. M. Steward, *J. Colloid Interface Sci.* **42** (U) (1973) 581, *ibid.*
- ⁷⁷J. L. Stakebake, *J. Nucl. Mat.* **38** (U) (1971) 241, *ibid.*
- ⁷⁸H. H. Van Tuyl, "Packaging of Plutonium for Storage or Shipment," internal report, Pacific Northwest Laboratory, Richland, Washington (U) (March 1981).
- ⁷⁹H. H. Van Tuyl, "Packaging of Plutonium for Storage or Shipment," (U) 1981, *ibid.*
- ⁸⁰J. D. Moseley and R. O. Wing, "Properties of Plutonium Dioxide," (U) 1965, *ibid.*
- ⁸¹J. L. Stakebake, "Determination of Plutonium Dioxide Surface Areas from X-Ray Crystal Sizes," *J. Catalysis* **78** (U) (1982) 477.
- ⁸²J. D. Moseley and R. O. Wing, "Properties of Plutonium Dioxide," (U) 1965, *ibid.*
- ⁸³H. H. Van Tuyl, "Packaging of Plutonium for Storage or Shipment," (U) 1981, *ibid.*
- ⁸⁴A. R. Kazanjian, P. M. Arnold, W. C. Simmons, and E. L. D'Amico, "Gas Generation Results and Venting Study for Transuranic Waste Drums," Rocky Flats Report RFP-3739, September 23, 1985 (U).
- ⁸⁵D. K. Roggenthen, T. L. McFeeters, and R. G. Nieweg, "Waste Drum Gas Generation Sampling Program at Rocky Flats," Rocky Flats Report PSD88-037, (U) (March 1989).
- ⁸⁶J. M. Haschke, et al., "The Reaction of Plutonium with Water: Kinetics and Equilibrium Behavior of Binary and Ternary Phases in the Pu+O+H System," 1983, *ibid.*
- ⁸⁷J. M. Haschke, "Hydrolysis of Plutonium: the Plutonium Oxygen Phase Diagram," 1992, *ibid.*
- ⁸⁸D. R. Horrell, et al., "A Study of Air in Pits: an Analytical Method (U)," (SRD) (1988), *ibid.*

~~SECRET~~
UNCLASSIFIED

UNCLASSIFIED
~~SECRET~~

June 17, 1993

- ⁸⁹G. Friedlander, J. W. Kennedy, and J. M. Miller, *Nuclear Radiochemistry*, 2nd ed., John Wiley and Sons, Inc., New York (U) (1966).
- ⁹⁰R. N. R. Mulford and B. A. Mueller, "Measurements of Helium Release from Materials Containing $^{238}\text{PuO}_2$," Los Alamos National Laboratory report LA-5215 (U) (July 1973).
- ⁹¹B. A. Mueller, D. D. Rohr, and R. N. R. Mulford, "Helium Release and Microstructural Changes in $^{238}\text{PuO}_2$," Los Alamos Scientific Laboratory report LA-5524 (April 1974).
- ⁹²M. F. Stevens, T. G. Zocco, and J. H. Steele, "Bubble-Void Formation in Delta Phase Plutonium (U)," Los Alamos National Laboratory document MST-5-88-9 (SRD) (August 25, 1988).
- ⁹³J. C. Martz, "Analysis of Plutonium Storage Pressure Rise," Los Alamos National Laboratory document NMT-5:92-328 (U) (July 1992).
- ⁹⁴J. L. Stakebake, D. T. Larson, and J. M. Haschke, *J. Alloys Comp.*, **202** (1993) 251, LA-UR-93-0040 (1993), *ibid.*
- ⁹⁵H. H. Van Tuyl, "Packaging of Plutonium for Storage or Shipment," (U) 1981, *ibid.*
- ⁹⁶J. M. Haschke and J. C. Martz, "Metal-Oxide Chemistry and Storage," presentation to the DOE workshop on plutonium storage, Los Alamos National Laboratory controlled publication LA-CP-93-159, Albuquerque, New Mexico (U) (May 26, 1993).
- ⁹⁷J. Lowe, private communication, Atomic Weapons Establishment, Aldermaston, UK (U) (December 17, 1992).
- ⁹⁸J. M. Haschke and J. C. Martz, "Metal-Oxide Chemistry and Storage," (U) (1993), *ibid.*
- ⁹⁹J. M. Haschke, "Evaluation of Source-Term Data for Plutonium Aerosolization," (U) (1992), *ibid.*
- ¹⁰⁰J. L. Stakebake and L. M. Steward, *J. Electro. Soc.* **119** (U) (1972) 730.
- ¹⁰¹J. C. Martz, J. M. Haschke, and J. L. Stakebake, "Plutonium Pyrophoricity," Los Alamos National Laboratory document LA-UR-93-2655, manuscript submitted to *J. Nucl. Mat.* (U) (1993).
- ¹⁰²J. L. Stakebake, *J. Less. Common Met.* **123** (U) (1986) 185.
- ¹⁰³J. L. Stakebake and M. R. Dringman, "Absorption of Oxygen on Sintered Plutonium Dioxide," *J. Nucl. Mat.* **23** (U) (1967) 349.
- ¹⁰⁴J. M. Haschke, "Evaluation of Source-Term Data for Plutonium Aerosolization," (U) (1992), *ibid.*
- ¹⁰⁵J. D. Moseley and R. O. Wing, "Properties of Plutonium Dioxide," (U) (1965), *ibid.*
- ¹⁰⁶D. Soderquist, J. Haschke, and J. Martz, "Fire Containment of Plutonium Metal," TPP Proposal submitted to DOE Complex 21 Reconfiguration Office, Los Alamos, New Mexico (U) (March 24, 1993).

~~SECRET~~
UNCLASSIFIED

UNCLASSIFIED
~~SECRET~~

June 17, 1993

- ¹⁰⁷J. Mishima, "Plutonium Release Studies II. Release from the Ignited Bulk Metallic Pieces," Battelle Pacific Northwest Laboratory report BNWL-357, Richland, WA (U) (November 1967).
- ¹⁰⁸J. Mishima, "Plutonium Release Studies I. Release from the Ignited Metal," Battelle Pacific Northwest Laboratory Report, Richland, WA, BNWL-205 (December 1965).
- ¹⁰⁹A. G. Philips and J. M. Haschke, "Use of Ceramic Coatings for Corrosion Protection," Rockwell International report CD88-1910, Golden, Colorado (U) (April 1988).
- ¹¹⁰F. H. Ellinger, et al., "Constitution of Plutonium Alloys," (U) (1968), *ibid*.
- ¹¹¹H. H. Van Tuyl, "Packaging of Plutonium for Storage or Shipment," (U) 1981, *ibid*.
- ¹¹²P. G. Stecher, et al., *The Merck Index, Seventh Edition*, (U) (1960), *ibid*.
- ¹¹³P. Jeal, private communication, Atomic Weapons Establishment, Aldermaston, UK (U) (February 11, 1993).
- ¹¹⁴J. C. Martz, J. M. Haschke, T. J. Beugelsdijk, and L. E. Bronisz, "Automation and Integration of Site-Return Processing," in *Nuclear Materials Technology: Weapons Complex 21 Reconfiguration*, Los Alamos National Laboratory document LALP-92-41 (U) (June 1992) p. 18.
- ¹¹⁵F. Berkhout, A. Diakov, H. Feiveson, H. Hunt, E. Lyman, M. Miller, and F. von Hippel, *Science & Global Sec.* 3 (U) (1993) 161.
- ¹¹⁶A. A. Dye, private communication, EG&G Rocky Flats Plant, Golden, Colorado (U) (June 1990).
- ¹¹⁷D. R. Harbur, J. W. Romero, and J. W. Anderson, "Plutonium-Cerium-Cobalt Fuel Development for Molten Reactors," *AFS Meetings: Modern Castings*, 48 (U) (1965) p. 124.
- ¹¹⁸D. R. Harbur, J. W. Anderson, and W. J. Maraman, "Studies on the U-Pu-Zr Alloy System for Fast Breeder Reactor Applications," Los Alamos Scientific Laboratory report LA-4512, (U) (November 1970).
- ¹¹⁹J. M. Haschke and J. C. Martz, "Storage of Plutonium Extracted from Weapons (U)," (1993), *ibid*.
- ¹²⁰J. D. Moseley and R. O. Wing, "Properties of Plutonium Dioxide," (U) (1965), *ibid*.
- ¹²¹G. Friedlander, J. W. Kennedy, and J. M. Miller, *Nuclear Radiochemistry*, 2nd ed., (U) (1966), *ibid*.
- ¹²²J. M. Haschke and J. C. Martz, "Storage of Plutonium Extracted from Weapons (U)," (SRD) (1993), *ibid*.
- ¹²³J. Richter, private communication at Los Alamos National Laboratory (SRD) (March 1993).
- ¹²⁴W. J. Ogle (DOE/OMA), T. J. Hiron (LANL), J. C. Mark (NRC), W. C. Myre (SNLA), and R. W. Selden (LLNL), "A DOE Special Study Report: Reactor Materials and Nuclear Explosives (U)," DOE Report, Washington, DC, DOE/DP-0003 (CNSI) (1978).

~~SECRET~~
UNCLASSIFIED

- ¹²⁵W. J. Ogle (DOE/OMA), T. J. Hirons (LANL), J. C. Mark (NRC), W. C. Myre (SNLA), and R. W. Selden (LLNL), "A DOE Special Study Report: Reactor Materials and Nuclear Explosives (U)," DOE report DOE/DP-0002, Washington, DC, (SRD) (February 1978).
- ¹²⁶W. J. Ogle, et al., "A DOE Special Study Report: Reactor Materials and Nuclear Explosives (U)," (SRD) (1978), *ibid*.
- ¹²⁷L. Gray, presentation to the DOE workshop on plutonium storage, Albuquerque, New Mexico (U) (May 26, 1993).
- ¹²⁸P. T. Cunningham, W. R. Dworzak, J. M. Haschke, and J. C. Martz, "Plutonium Disposition and Pit Disassembly," presentation to the National Academy of Sciences Committee on International Security and Arms Control, Los Alamos, New Mexico (SRD) (March 31, 1993).
- ¹²⁹J. M. Haschke and J. C. Martz, "Storage of Plutonium Extracted from Weapons (U)," Los Alamos National Laboratory report LA-12557-MS, (SRD) (1993), *ibid*.
- ¹³⁰W. J. Ogle, et al., "A DOE Special Study Report: Reactor Materials and Nuclear Explosives (U)," (SRD) (1978), *ibid*.
- ¹³¹J. M. Haschke and J. L. Stakebake, "Decomposition Kinetics of Plutonium Hydride," in *The Rare Earths in Modern Science and Technology Vol. 2*, G. J. McCarthy, J. J. Rhyme, and H. B. Selber, Eds., Plenum Publishing Corp, New York (U) (1980) p. 577.
- ¹³²J. M. Cleveland, *The Chemistry of Plutonium*, (U) (1979), *ibid*.
- ¹³³J. M. Cleveland, *The Chemistry of Plutonium*, 1 (U) (1979), *ibid*.
- ¹³⁴J. C. Mark, "Use of Reactor Grade Plutonium in Weapons (U)," Los Alamos Scientific Laboratory report LA-3287-MS (April 8, 1965) (SRD).
- ¹³⁵R. W. Selden, "Reactor Plutonium and Nuclear Explosives," presentation to representatives of the IAEA (November 1976). Available as Los Alamos National Laboratory internal memorandum IT-2 (U)-92-383 (NIS).
- ¹³⁶J. C. Mark, "Reactor-Grade Plutonium's Explosive Properties," A publication of the Nuclear Control Institute, NPT/95 (U) (August 1990).
- ¹³⁷J. C. Mark, "Use of Reactor Grade Plutonium in Weapons (U)," (SRD) (1965), *ibid*.
- ¹³⁸J. W. Gordon, "Notes of the Non-Proliferation Nuclear Weapons Working Group (U)," Los Alamos Memorandum IT-2(S)-92-380, Los Alamos, NM (December 1992) (SRD).
- ¹³⁹J. M. Haschke, "Site Return Processing Overview, " in *Nuclear Materials Technology: Weapons Complex 21 Reconfiguration*, Los Alamos National Laboratory report LALP-92-41 (U) (June 1992), p. 13.
- ¹⁴⁰K. M. Gruetzmacher, "Site Waste for TASP Pu Flowsheet," unpublished Los Alamos National Laboratory Report (U) (January 1992).
- ¹⁴¹M. C. Bronson, private communication, Lawrence Livermore National Laboratory, Pu-TASP working group, Livermore, CA (CRD) (June 1991).

UNCLASSIFIED
~~SECRET~~

June 17, 1993

- ¹⁴²J. L. Stakebake, "Kinetic Studies of the Reaction of Plutonium Hydride with Oxygen," *Nucl. Sci. Eng.* **78** (U) (1981) 386.
- ¹⁴³D. L. Brandt, private communication, Los Alamos National Laboratory, (U) (May 1993).
- ¹⁴⁴K. K. S. Pillay and D. C. Christensen, "Residue and Waste Issues," presentation to DOE DP-42, Washington, DC (U) (March 15, 1993).
- ¹⁴⁵T. F. Drouillard, "Acoustic Emission Monitoring of a Hydride Experiment," Rockwell International report CD82-3939, Golden, Colorado (SRD) (October 1982).
- ¹⁴⁶C. R. Heipel, S. H. Carpenter, D. R. Horrelll, and T. F. Drouillard, "Acoustic Emission Monitoring of Plutonium Hydriding," EG&G Rocky Flats Report CD89-00425, Golden, Colorado (SRD) (September 1989).
- ¹⁴⁷J. M. Haschke and T. H. Allen, "Hydrogen Corrosion of Plutonium in Nuclear Weapons (U)," (SRD) (1992), *ibid.*
- ¹⁴⁸H. H. Van Tuyl, "Packaging of Plutonium for Storage or Shipment," (SRD) (1981), *ibid.*
- ¹⁴⁹L. Gray, presentation to the DOE workshop on plutonium storage, Albuquerque, NM (U) (May 26, 1993).
- ¹⁵⁰P. T. Cunningham, et al., "Plutonium Disposition and Pit Disassembly," (SRD) (1993), *ibid.*
- ¹⁵¹J. M. Haschke and J. C. Martz, "Metal-Oxide Chemistry and Storage," (U) 1993, *ibid.*

~~SECRET~~
UNCLASSIFIED

UNCLASSIFIED
~~SECRET~~

LA-12624-MS

June 17, 1993

DISTRIBUTION

No. of Copies

- 3 U.S. Department of Energy
M/S MA 232.21, Energy Library (3 copies)
Attn: T&A
P.O. Box A
Germantown, MD 20874
- 12 U.S. Department of Energy
P.O. Box 23865
Washington, D.C. 20026
For: Alessi, Vic, AN-1
Bieniawski, Andrew J., AN-10
Bradshaw, Gail L., AN-10
Canter, Howard, DP-40
Chan, Lisa, K. DP-40/42
Czajkowski, Tony, AN-1
Goldman, Ira N., AN-30
Koontz, Max A., AN-10
Nelson, Ronald D., DP-40
Ogle, W. J., OMA
Sanders, Ken, E. AN-30
Willett, Lew R., DP-27
- 1 U.S. Department of Energy
Technical Information
P.O. Box 62
Oak Ridge, TN 37831
- 1 U.S. Department of Energy
Attn: I. Williams, OMA, DP-242.1
P.O. Box A
Germantown, MD 20874
- 2 U.S. Department of Energy (Albuquerque Operations Office)
Attn: TA Station (1 copy)
P.O. Box 5400
Albuquerque, NM 87115
For: Stephen J. Guidice (1 copy)

~~SECRET~~
UNCLASSIFIED

UNCLASSIFIED
~~SECRET~~

LA-12624-MS

June 17, 1993

128

Los Alamos National Laboratory
Attn: Report Library (6 copies)
Mail Station 5000
P.O. Box 1663
Los Alamos, NM 87545

For: Siegfried S. Hecker, DIR, MS A100

Adams, Peter J., X-2, MS B220
Allen, Thomas H., NMT-5, MS E506
Austin, Larry R., EM/WM, MS J591
Baran, James Andrew, NIS-9, MS B229
Barlich, Albert H., NIS-8, MS B228
Becker, Stephen A., X-2, MS B220
Bement, Thomas R., TSA-1, MS F600
Bernardin, Michael P., X-5, MS B259
Brandt, Dennis Lee, NMT-4, MS E513
Brownell, John H., X-5, MS B259
Bryson, Maurice C., NIS, MS F650
Caramana, Edward J., X-4, MS F664
Castain, Ralph H., NIS-4, MS D448
Charmatz, Albert W., NIS-9, MS B229
Christensen, Dana C., NMT-DO, MS E500
Close, Donald A., NIS-6, MS J562
Cobb, Donald D., NIS, MS F650
Cunningham, Paul T., PDNMRT, MS A102
Dewey, Harry J., CST-1, MS J565
Dworzak, Wolfgang R., NMT-DO, MS E500
Forehand, Harry M., NIS-8, MS B228
Gerwin, Richard J., T-15, MS K717
Giebink, David Robert, P-24, MS D406
Giles, Joseph C., NIS, MS F650
Gordon, James W., NIS-9, MS B229
Gorman, Thomas J., X-4, MS F664
Gutierrez, Rueben L., NMT-5, MS E506
Hanson, Earl Marie, PDNMRT, MS A102
Harbur, Delbert R., NMT-DO, MS D419
Haschke, John M., NMT-5, MS E506
Hartford, Jr., Allen, DSTBP, MS F671
Hawkins, Houston T., NIS, MS F650
Heath, Alexandra R., X-6, MS B226
Henderson, Michael G., DDTSA, MS F606
Henry, Carl Noel, NIS, MS F670
Henson, Robert M., NIS-9, MS B229
Hill, George Grant, DDESA, MS P945
Hill, Jeffrey P., ESA-DE, MS C932
Hirons, Thomas J., EM/DOE/FP, MS J591
Immele, John D., PDNW, MS A105
Jain, Mahavir, FSS-16, MS B259
Johnson, M. William, NIS-6, MS J562
Johnson, R. Douglas, X-4, MS F664
Juzaitis, Raymond J., DDX, MS B218
Kelly, Maxie Main, ESA-WE, MS C936
Kim, Kyu C., NMT-DO, MS E510
Kinkead, Scott, CST-7, MS J534
Koym, Jr., Vernon R., NIS-9, MS B229

51

~~SECRET~~ UNCLASSIFIED

UNCLASSIFIED
~~SECRET~~

June 17, 1993

Krajcik, Richard A., DDX, MS B218
LaDelfe, Peter C., NIS-2, MS D436
Linford, Rulon K., DSTBP, MS F673
Lucas, Marcia C., NIS-SG, MS E550
MacInnes, Michael R., NIS-8, MS B228
Mah, Richard, EM OUTREACH, MS J547
Malanify, John J., NIS-6, MS J562
Markin, Jack T., NIS-7, MS E541
Martz, Joseph C., NMT-5, MS E506 (20 copies)
Matthews, R. Bruce, DDNMT, MS E500
McKerley, Bill J., NMT-DO, MS E501
Morgan, Jerry Allen, DX-13, MS P940
Morris, Clifford D., X-2, MS B220
Neil, Charles H., X-4, MS F664
Petranto, Joseph J., ESA-WE, MS C936
Phillips, John R., CST-8, MS G740
Pillay, K. K. Sivasankara, NMT-DO, MS E500
Pogue, Edward W., DX-13, MS P940
Richter, John L., X-5, MS B259
Riley, Ralph A., NIS-9, MS B229
Rinehart, Gary H., NMT-9, MS E502
Rogers, Jr., Brown B., X-4, MS F664
Salimi, Behzad, X-4, MS F664
Sandford, Thomas A., NIS-8, MS B230
Schultz, Rodney B., DDX, MS B218
Sharp, Renida R., ESA-EA, MS C931
Sherwood, Jane C., NIS-9, MS B229
Solem, Johndale C., DDT, MS B210
Soran, Diane M., NIS, MS B224
Stanbro, William D., NIS-7, MS E541
Stephens, John R., CST-1, MS J565
Sterbenz, Stephen M., P-23, MS D406
Stevens, Michael F., CMS, MS K765
Strickfaden, Gerald E., NIS-9, MS B229
Suchocki, Thomas P., NIS-9, MS B229
Thurston, Rodney S., NIS-9, MS B229
Trapp, Turner J., NMRT-NM, MS F628
Trulock, III, Notra, NIS, MS F650
Urban, William T., X-6, MS B226
Vandermaat, Paul X-2, MS B220
Varley, Daniel T., DDESA, MS P945
Wallace, Peter L., NMT-DO, MS E500
Watson, Clayton W., MS P940
Weaver, Thomas A., EES-3, MS C335
Webb, Michael P., NIS-9, MS B229
Wehner, Thomas R., TSA-3, MS F607
White, Paul C., PDNW, MS F670
White, Stephen W., X-6, MS B226
Williams, Joel D., NMT-2, MS E511
Wilson, K. Boyd, NIS-9, MS B229
Wood, Merri M., X-2, MS B220
Wood, Warren T., NRMT-NM, MS E524
Worlton, Dale Reid, X-4, MS F664
Young, Richard J., X-4, MS F664

~~SECRET~~
UNCLASSIFIED

UNCLASSIFIED
~~SECRET~~

June 17, 1993

- 1 Sandia National Laboratories
Attn: Mail Services Section
P.O. Box 5800
Albuquerque, NM 87185
For: Technical Library (1 copy)
- 9 University of California
Lawrence Livermore National Laboratory
Attn: Technical Information Department
Mail Stop L-313
P.O. Box 808
Livermore, CA 94550
For: Library, Reports Section (2 copies)
Bronson, Mark C., L 439
Dunlop, Bill H., L 205
Kiernan, Gerald P., L 205
Kovar, Fred R., L 024
Robbins, Jack L., L 125
Staehle, George G., L 389
Sunwoo, Ann, L 342
- 2 Director
Defense Nuclear Agency
Attn: CSAO (2 copies)
6801 Telegraph Rd.
Alexandria, VA 22310-3398
- 1 Commander
Field Command, Defense Nuclear Agency
Attn: FCIESC
1680 Texas Street, SE
Kirtland, AFB, NM 87117-5669
For: Bettye J. Garbutt
- 1 Phillips Lab Technical Library
PL/SUL
3550 Aberdeen Ave., S.E.
Kirtland AFB, NM 87117-5776
- 1 Martin Marietta Energy Systems, Inc.
Y-12 Plant Records Department,
Bldg. 9711-5
P.O. Box 2009
Oak Ridge, TN 37831-8169
For: Stanley D. Moses (for Wolfgang Panofsky)
- 1 Office of Science & Technology Policy
Science Advisor to the President
Old Executive Office Building
Washington, DC 20503

~~SECRET~~
UNCLASSIFIED

UNCLASSIFIED
~~SECRET~~

~~SECRET~~
UNCLASSIFIED

UNCLASSIFIED
~~SECRET~~

LOS ANGELES NAT'L LAB.
LID. REPT. COLLECTION
RECEIVED

'95 SEP 14 AM 4 47

~~SECRET~~
UNCLASSIFIED